

FACESTOCK DESCRIPTION: 60# AVON BRILLIANT WHITE CLASSIC CREST® SMOOTH WET STRENGTH

Elegant bright white smooth finish with an exceptionally clean and crisp appearance. It is a great stock for premium labeling such as wine bottles and home-craft labeling. The base paper is also FSC® certified, acid free and archival quality. It is manufactured with "wet strength" properties to increase performance in moist environments.

Basis Weight (25 x 38 / 500), lbs.	60
Caliper, mils	4.4
Brightness, MacBeth, %	93
Opacity, Huygen, %	94
Smoothness, Sheffield, units	125
Regulatory Compliances	ASTM F963 Child Toy Safety, California Proposition 65, CONEG, FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to, RoHS

FSC® is a registered trademark of Forest Stewardship Council™.

Classic Crest® is a registered trademark of Neenah Paper, Inc.

ADHESIVE DESCRIPTION:

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Adhesive designed for face and back label use on glass bottles and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles and hot water removability depending on face, substrate, water temperature, and dwell time.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	+25
Service Temperature Range, °F	-10 to +200
Regulatory Compliances	Acute Oral Toxicity 16 CFR 1500.3, ASTM F963 Child Toy Safety, CONEG, FDA 21 CFR 175.105, Primary Eye Irritant 16 CFR 1500.42, Primary Skin Irritant 16 CFR 1500.41, REACH, RoHS

LINER DESCRIPTION: 44#

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and application.

Basis Weight (25 x 38 / 500), lbs.	48# +/- 10%
Caliper, mils	3.2 +/- 10%
Regulatory Compliances	CONEG, REACH, RoHS

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: Six months when stored at 72°F / 50% RH.

Updated: April 2014